

Przegląd

Informacje o produkcie



DGBSC-SG02/4-10080000436

Building wiring terminals, Rated current: 32A. Rated voltage (III/2) : 450V, max. 4 mm², Color: transparent, Contact surface : Tin

Zalety produktu

- ☒ Rotatable operating handle, easy to operate
- ☒ Suitable for all conductors types
- ☒ Suitable for field wiring, saving installation time

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

□

Connection capacity

Conductor cross section solid	0.2~4mm²
Conductor cross section flexible	0.2~4.0mm²
AWG	24~12AWG
Strip length	12mm

Electrical parameters UL

Rated voltage (C)	600V
-------------------	------

Electrical parameters IEC

Rated voltage	450V
Rated current	32A
Rated current(III/2)	450V

Rated power frequency voltage(1min)	2.5KV
Item properties	
Connection method	Push-in spring connection
Number of potentials	2
Pluggable or not	no
Number of rows	1
Material data	
Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PC
Shell color	Transparent
Flammability rating	UL94V-2
Environmental data	
Ambient temperature (operation)	-40℃~85℃

Akcesoria

Dane biznesowe	
numer zamówienia	10080000436
Jednostka opakowania	100
Minimalna ilość zamówienia	
Waga produktów (bez opakowania)	3.22

