

Przegląd

Informacje o produkcie



5EDGKHR-7.62-10010009638

Pluggable terminal blocks, Rated current: 41A. Rated voltage
(III/2) : 1000V, pitch: 7.62mm, Color: Green, Contact surface : Tin

Zalety produktu

- ☒ Well-known mounting principle allows worldwide use
- ☒ Can be connected to 5EDGKH-7.62, 5EDGA/B-7.62 series connectors to meet diverse connection needs
- ☒ Reverse connector, providing anti touch protection for device output or free hanging line to line connections
- ☒ Keying parts can be installed

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Packaging information

Type of packaging

box-packed

Connection capacity

Conductor cross section solid

0.2~6mm²

Conductor cross section flexible

0.2~6.0mm²

feeler gauge a x b / diameter

3.6mm x 3.1mm / 3.4mm

AWG

24~8AWG

Torque

0.8N.m

Strip length

10mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated current (B)	41A
Rated current (C)	41A

Electrical parameters IEC

Rated voltage	1000V
Rated current(III/3)	1000V
Rated current	41A
Rated current(III/2)	1000V
Rated current(II/2)	1000V
Rated surge voltage(III/3)	8KV
Rated surge voltage(III/2)	8KV
Rated surge voltage(II/2)	6KV

Item properties

Connection direction	0°
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	7.62mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Relative tracking index CTI	600V
Glow Wire Flammability Index GWFI	850
Glow wire ignition temperature GWIT	750
Ball pressure test temperature	125°C
Shell color	green
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Akcesoria

Tool

Screwdriver	0.6x3.5,Slotted screwdriver
Operating tool	/

Accessories

Coding strip	5EDG-PWI
Bridge	/
Marking strip	/

Others

/

Dane biznesowe

numer zamówienia	10010009638
Jednostka opakowania	425
Minimalna ilość zamówienia	
Waga produktów (bez opakowania)	7.65