

Przegląd

Informacje o produkcie



9EDGKD-HC-7.5-10020007568

Pluggable terminal blocks, Rated current: 25A. Rated voltage
(III/3) : 630V, pitch: 7.5mm, Color: black, Contact surface : Tin

Zalety produktu

- ☒ Push-in spring connection, easy wiring
- ☒ SNAP-LOCK series, with self-locking buckle

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Packaging information

Type of packaging

box-packed

Connection capacity

Conductor cross section solid

1.0~6mm²

Conductor cross section flexible

1.0~6.0mm²

AWG

18~10AWG

Strip length

12mm

Electrical parameters UL

Rated voltage (B)

600V

Rated voltage (C)

600V

Rated current (B)	25A
Rated current (C)	25A

Electrical parameters IEC

Rated voltage	800V
Rated current(III/3)	630V
Rated current	25A
Rated current(III/2)	800V
Rated current(II/2)	1000V
Rated surge voltage(III/3)	6KV
Rated surge voltage(III/2)	6KV
Rated surge voltage(II/2)	6KV

Item properties

Connection method	Push-in spring connection
Pitch	7.5mm
Number of potentials	4
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Relative tracking index CTI	600V
Glow Wire Flammability Index GWFI	850
Shell color	Black

Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC61984/ UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Akcesoria	
Tool	
Screwdriver	/
Operating tool	/
Accessories	
Coding strip	2EDG-PWI
Bridge	/
Marking strip	/
Others	/

Dane biznesowe	
numer zamówienia	10020007568
Jednostka opakowania	240
Minimalna ilość zamówienia	
Waga produktów (bez opakowania)	13.2